

(12) UK Patent Application (19) GB (11) 2 139 181 A

(43) Application published 7 Nov 1984

(21) Application No 8411020

(22) Date of filing 30 Apr 1984

(30) Priority data

(31) 8312138
8318028

(32) 4 May 1983
2 Jul 1983

(33) GB

(51) INT CL³
G09F 3/02 A47J 51/08

(52) Domestic classification
B8F BC
A4L 121 AF

(56) Documents cited
None

(58) Field of search
B8F
A4L

(71) Applicant
Morplan (United Kingdom),
40 Queensway, Enfield, Middlesex EN3 4SP



(72) Inventor
William John Edwards

(74) Agent and/or Address for Service
G. F. Redfern & Co.,
Marlborough Lodge, 14 Farncombe Road, Worthing,
West Sussex BN11 2BT

(54) Fitments for mounting on coat hangers






(57) A fitment is in the form of a right circular cylinder consisting of two portions (1 and 2) hingedly connected to one another by a web (11) of synthetic resin material. In the embodiment illustrated, the portion (1) has a semi-circular head (3), a semi-circular base (4) and a semi-circular intermediate platform (5). Similarly the portion (2) has a semi-circular head (6), a semi-circular base (7) and a semi-circular intermediate platform (8). Each of the head, base and intermediate platform portions is provided with a semi-circular recess, of which two are indicated at (9) and (10). The intermediate platform (5) is provided with a projecting pin (12) and the intermediate platform (8) is provided with a recess (13).

When the tally is in use, the two portions are clipped together around the hook (14) of a hanger (15). The pin and the recess may be designed so that, once they have been engaged, they cannot be disengaged without destruction, or alternatively they may be designed so that they can be disengaged.



BEST AVAILABLE COPY

GB 2 139 181 A



SPECIFICATION

Improvements in or relating to fitments for mounting on coat hangers

5 This invention relates to fitments for use on coats hangers of the general kind described and claimed in United Kingdom Patent Specification 1 397 413.

10 The said Patent Specification describes and claims a garment identification tally removably mounted on a coat hanger, said tally being generally in the form of a right cylinder, the wall or walls of which surround a hollow space, and the head of which is provided with an axial hole, through which the hook
15 of the hanger passes, wherein the generated wall or walls of the cylinder are provided with a plurality of identification markings arranged side by side around the axis of the cylinder in such a way that at least one of said markings is visible from any angular position
20 around said axis, and wherein the axial hole is so dimensioned in relation to the hook of the hanger that the tally rests on the shoulder of the hanger without tilting.

25 A tally in accordance with the said Patent specification is fitted on to a coat hanger by passing the free end of the coat hanger hook through the axial hole in the tally and manoeuvring the tally round the bends in the hook until it rests on the shoulder of the hanger. It is an object of the present invention to
30 provide a fitment which does not need to be or, in certain cases indeed, cannot be, threaded on to the hook.

35 From one aspect the present invention consists in a fitment for mounting on a coat hanger, said fitment being generally in the form of a right cylinder having a head and consisting of two portions hingedly connected one to the other along a hinge axis located in the, or a, generated wall of the cylinder, wherein each portion of the said head is provided
40 with a recess adapted, when the two hinged portions are adjacent to one another, to form an axial hole and wherein locking means are provided to maintain said hinged portions adjacent to one another, with the hook of the hanger passing through said axial
45 hole.

On embodiment of the invention is used as a garment identification tally. In this embodiment, as in the case of a tally in accordance with said Patent Specification, the generated wall, or walls, of the
50 cylinder is, or are, provided with a plurality of identification markings arranged side by side around the axis of the cylinder normally in such a way that at least one of said markings is visible from any angular position around said axis. In some cases it
55 may be sufficient to provide two identification markings, but normally it will be preferred that three or four identification markings should be provided. Alternatively, or in addition, identification may be provided, or assisted, by colour coding of the
60 material of which the tally is made.

If desired, the right cylinder may have a base as well as a head and, in this case, each portion of said base, as well as each portion of the head, is provided with a substantially semi-circular recess adapted,
65 when the two hinged portions are adjacent to one

another, to form an axial hole through which the hook of the coat hanger can pass.

70 The fitment may also be provided with an intermediate platform located mid-way between said head and said base. In this case, each portion of the platform is also provided with a semi-circular recess and, when the two hinged portions of the tally are adjacent to one another, the two semi-circular recesses in the platform form an axial hole similar to the axial holes in the head and the base.

75 In another embodiment of the invention the right cylinder has no base. However in this case it is still possible to provide the intermediate platform. As in the case of the embodiment having the head, the
80 base and the intermediate platform, the intermediate platform consists of two portions, each of which is provided with a recess arranged so that, when the two hinged portions are adjacent to one another, the two recesses in the platform form a hole, coaxial
85 with the hole in the head.

In some cases it is desirable that the fitment should not be removable from the hook of the hanger without being destroyed in the process. This is particularly the case when the fitment is used as a
90 garment identification tally. In certain uses of the tally it may suffer from the disadvantage that it can be removed from the hook of the hanger by children, staff or anyone else who cares to tamper with it. Thus, in this case, the tally is designed so that it
95 cannot be manoeuvred round the bends in the hook, and the locking means are arranged so that, once they have been engaged, they cannot be disengaged without destroying the fitment. It is to be understood that it will normally be impossible to manoeuvre the
100 tally round the bends if the tally is provided with a base, or an intermediate platform, as well as a head. This is particularly the case if the tally has both a base and an intermediate platform.

In other uses of a fitment in accordance with the
105 invention it can be advantageous to design the fitment so that it is removable, and hence re-usable. For this purpose the locking means are modified in such a way that the two hinged portions can be separated, if so desired, although they are normally
110 held sufficiently firmly together to retain the fitment on the hook of the hanger. Alternatively, or in addition, if the base and the intermediate platform are omitted, it is possible to remove the fitment by manoeuvring it round the bends in the hook.

115 As has already been mentioned, one use for a fitment in accordance with the invention is as a garment identification tally. However fitments in accordance with the invention are not limited to that particular use. In particular it has been found that,
120 with the very narrow profile coat hangers which are now sometimes used, the spacing between garments hung on a series of coat hangers on a rail is insufficient for the garments to hang free of each other and hence bunching can occur which can
125 cause the garments to crease unduly. Accordingly, in these circumstances, a fitment in accordance with the present invention may be used solely to provide adequate separation between adjacent coat hangers on a garment rail.

130 Preferably the diameter of each hole in the head,

BEST AVAILABLE COPY

and also of the holes in the base and the intermediate platform when provided, is substantially equal to the diameter of the hook of the hanger with which the tally is to be used, so that once the two portions of the tally have been locked into their adjacent position the tally grips the hook firmly.

Preferably a tally in accordance with the invention is made of synthetic resin material, for example polypropylene. The use of synthetic resin material enables the hinge between the two portions to consist of a thin web of the same material so that the two portions can be moulded in a single operation.

The locking means may comprise a pin projecting from one portion and a recess provided in the other portion. The pin may be held in the recess solely because it is a friction fit, but preferably the free end of the pin is provided with a barb, or the like, which engages in a slot in the recess so that, once the shoulders of the barb have engaged in the slot, the two portions cannot be separated without breaking the barb or the pin.

Preferably the head and the base of the tally are circular, and each of the two portions is semi-circular.

A tally in accordance with the invention which is designed so that, once it has been fitted on to a hanger, it cannot be removed therefrom without being destroyed, is particularly suitable for use with disposable hangers, i.e. hangers which are given away with the garment which is displayed thereon in a shop or the like. One way at the present time of marking disposable hangers is to attach an adhesive label thereto. A tally in accordance with the invention is easier to apply to a hanger than an adhesive label and, in addition, it is a better visual aid for the customer than an adhesive label. In particular a tally in accordance with the invention is located above the garment on the hanger, whereas the adhesive label may be obscured by the collar of the garment.

The invention will now be more particularly described in connection with the accompanying diagrammatic drawings, in which:

Figure 1 is a perspective view of a tally in accordance with the invention in the open position in which it is manufactured;

Figure 2 is a perspective view of the tally illustrated in *Figure 1* after it has been mounted on the hook of a coat hanger;

Figure 3 is a scrap view, partly in section, showing the locking device of the tally illustrated in *Figures 1* and *2*;

Figure 4 is a scrap view, partly in section, showing the hinge of the tally illustrated in *Figures 1, 2* and *3*, and

Figure 5 is a scrap view, partly in section, of a modification of the locking means illustrated in *Figure 3*.

In the tally illustrated in *Figures 1* to *4*, the body consists of two generally semi-circular portions *1* and *2*. The portion *1* has a semi-circular head *3*, a semi-circular base *4* and a semi-circular intermediate platform *5*. Similarly the portion *2* has a semi-circular head *6*, a semi-circular base *7* and a semi-circular intermediate platform *8*. Each of the heads, bases and intermediate platforms is provided

with a semi-circular recess, of which two are indicated at *9* and *10*.

The two portions *1* and *2* are interconnected by a web *11* which constitutes a hinge. Further, the intermediate platform *5* is provided with a projecting pin *12*, and the intermediate platform *8* is provided with a recess *13*.

As can be seen from *Figure 2*, when the tally is in use, the two portions are clipped together around the hook *14* of a coat hanger *15*. The wall of each of the portions *1* and *2* is provided with two identification markings, of which two can be seen at *16* and *17*.

As can be seen from *Figure 3*, the free end of the pin *12* is generally conical, and forms a barb *18* having a shoulder *19*. When the two portions are locked together, as shown in *Figure 3*, the shoulder *19* is retained in a slot *20*.

The modified locking means illustrated in *Figure 5* again consists basically of a recess *13* in the portion *2* and a projecting pin *12* forming part of the portion *1*. However, in the present instance, the diameter of the pin *12* is less than the diameter of the recess *13* except that the pin *12* is provided with an enlarged portion *21*, while the recess *13* is provided with a portion of reduced diameter *22*. The edges of the portions *21* and *22* are curved so that the pin *12* can readily be pushed into the recess *13* so that the enlarged portion *21* passes the portion *22*. In this position (which is illustrated in *Figure 3*) the two hinged portions of the fitment are held securely together. However, because of the curved profiles of the portions *21* and *22*, and the nature of the material of the fitment, the two hinged portions can be separated if sufficient force is applied thereto without damaging the fitment, and in particular without breaking the pin *12* away from the portion *1*. Thus, if desired, the fitment can readily be removed from one coat hanger and clipped on to another hanger.

While the invention has been illustrated in connection with a tally having a circular head and a circular base it is, of course, to be understood that, as in the case of the tally described and claimed in the said Patent Specification, the head and base may have any desired shape. In particular the head and base may be square, and in this case the hinge is preferably provided in one of the corners of the squares so that the two portions of the head and the base will be in the form of isosceles triangles.

The invention has also been illustrated in connection with a tally having a base and an intermediate platform as well as a head. However, as already explained, it is to be understood that the base of the intermediate platform, or the base and the intermediate platform, may be omitted in certain embodiments of the invention.

CLAIMS

1. A fitment for mounting on a coat hanger, said fitment being generally in the form of a right cylinder having a head and consisting of two portions hingedly connected one to the other along a hinge axis located in the, or a, generated wall of the cylinder, wherein each portion of the said head is

provided with a recess adapted, when the two hinged portions are adjacent to one another, to form an axial hole and wherein locking means are provided to maintain said hinged portions adjacent to one another, with the hook of the hanger passing through said axial hole.

2. A fitment as claimed in Claim 1 for use as a garment identification tally, wherein the generated wall, or walls, of the cylinder is, or are, provided with a plurality of identification markings arranged side by side around the axis of the cylinder in such a way that at least one of said markings is visible from any angular position around said axis.

3. A fitment as claimed in Claim 1 or Claim 2 for use as a garment identification tally, wherein identification is provided, or assisted, by colour coding of the material of which the tally is made.

4. A fitment as claimed in any of the preceding Claims, wherein the right cylinder has a base as well as a head, and wherein each portion of said base, as well as each portion of said head, is provided with a substantially semi-circular recess adapted, when the two hinged portions are adjacent to one another, to form an axial hole.

5. A fitment as claimed in Claim 4, wherein the right cylinder is also provided with an intermediate platform located substantially mid-way between said head and said base, and wherein each portion of said platform is also provided with a semi-circular recess adapted, when the two hinged portions are adjacent to one another, to form an axial hole.

6. A fitment as claimed in any of Claims 1 to 3, wherein the right cylinder has no base but does have a platform intermediate the two ends of the cylinder, said platform consisting of two portions, each of which is provided with a semi-circular recess adapted, when the two hinged portions are adjacent to one another, to form an axial hole.

7. A fitment as claimed in any of the preceding Claims which is not removable from the hook of the hanger without being destroyed in the process.

8. A fitment as claimed in Claim 7, wherein the right cylinder includes a base or an intermediate platform, or a base and an intermediate platform, in addition to the head, and wherein the diameter of the axial holes is such that the fitment cannot be manoeuvred round the bends in the hook of the hanger.

9. A fitment as claimed in Claim 8, wherein said locking means are arranged so that, once they have been engaged, they cannot be disengaged without destroying the fitment.

10. A fitment as claimed in any of Claims 1 to 6, wherein the locking means are arranged so that the two hinge portions can be separated, if so desired, after the locking means have been engaged, although they are normally held sufficiently firmly to retain the fitment on the hook of the hanger.

11. A fitment as claimed in any of the preceding Claims, made of synthetic resin material.

12. A fitment as claimed in Claim 11, wherein said synthetic resin material is polypropylene.

13. A fitment as claimed in Claim 11 or Claim 12, wherein the hinge between the two portions consists of a thin web of the synthetic resin material so that

the two portions can be moulded in a single operation.

14. A fitment as claimed in any of the preceding Claims, wherein the locking means comprise a pin projecting from one portion and a recess provided in the other portion.

15. A fitment as claimed in Claim 14, wherein, once the locking means have been engaged, the pin is held in the recess solely because it is a friction fit.

16. A fitment as claimed in Claim 14, wherein the free end of the pin is provided with a barb, or the like, which engages in a slot in the recess.

17. A fitment as claimed in Claim 16, wherein the barb and the slot are so designed that, once the shoulders of the barb have engaged in the slot, the two portions cannot be separated without breaking the barb or the pin.

18. A fitment as claimed in any of the preceding Claims, wherein the cylinder is a right cylinder and each of the two portions is semi-circular.

19. A fitment for mounting on coat hangers substantially as hereinbefore described with reference to, and as illustrated in, any of the accompanying diagrammatic drawings.

20. A garment identification tally substantially as hereinbefore described with reference to, and as illustrated in, any of the accompanying diagrammatic drawings.

Printed in the UK for HMSO, D8818835, 8/84, 7102.
Published by The Patent Office, 25 Southampton Buildings, London,
WC2A 1AY, from which copies may be obtained.

THIS PAGE BLANK (USPTO)